CSE 392/CS 395T/M 397C: Matrix and Tensor Algorithms for Data

Instructor: Shashanka Ubaru

University of Texas, Austin Spring 2025

Lecture 23: Randomized t-SVD, t-product applications

Outline

1 Randomized t-SVD

2 t-product applications

- Face Recognition
- Tensor Neural Network
- Tensor Graph Neural Networks

t-SVD

Theorem: For $\mathcal{A} \in \mathbb{R}^{m \times \ell \times n}$ there exists a full tensor-SVD

$$\mathcal{A} = \mathcal{U} * \mathcal{S} * \mathcal{V}^{\top},$$

with $m \times m \times n$ orthogonal tensor \mathcal{U} , $\ell \times \ell \times n$ orthogonal tensor \mathcal{V} , and $m \times \ell \times n$ f-diagonal tensor \mathcal{S} ordered such that the singular tubes $\mathbf{s}_i = \mathcal{S}_{i,i,:}$ have $\|\mathbf{s}_1\|_F^2 \ge \|\mathbf{s}_2\|_F^2 \ge \cdots$.



The **t-rank** is the number of non-zero tube-fibers in \mathcal{S} .

The t-SVD can be computed efficiently (in parallel) by moving to the Fourier domain.

- Compute $\widehat{\mathcal{A}}$
- For i = 1, ..., n, find matrix SVD of each frontal slice: $\widehat{\mathcal{U}}_{:,:,i}\widehat{\mathcal{S}}_{:,:,i}\widehat{\mathcal{V}}_{::,i}^H = \widehat{\mathcal{A}}_{:,:,i}$
- To get $\mathcal{U}, \mathcal{S}, \mathcal{V}$, inverse FFT along tube fibers of $\widehat{\mathcal{U}}, \widehat{\mathcal{S}}, \widehat{\mathcal{V}}$.

Tensor-tensor SVDs

Theorem (Kilmer, Horesh, Avron, Newman)

Let \mathcal{A} be a $m \times p \times n$ tensor and \mathbf{M} a non-zero multiple of a unitary/orthogonal matrix. The (full) \star_M tensor SVD (t-SVDM) is

$$\mathcal{A} = \mathcal{U} \star_M \mathcal{S} \star_M \mathcal{V}^{\mathrm{H}} = \sum_{i=1}^{\min(m,p)} \mathcal{U}_{:,i,:} \star_M \mathcal{S}_{i,i,:} \star_M \mathcal{V}_{:,i,:}^{\mathrm{H}}$$

with $\mathcal{U}, \mathcal{V} \star_M$ -unitary, $\mathfrak{C} \|\mathcal{S}_{1,1,:}\|_F^2 \geq \|\mathcal{S}_{2,2,:}\|_F^2 \geq \dots$



$$\begin{split} &\widehat{\mathcal{A}} \leftarrow \mathcal{A} \times_{3} \boldsymbol{M} \\ &i = 1, \dots, n \\ &[\widehat{\mathcal{U}}_{:,:,i}, \widehat{\mathcal{S}}_{:,:,i}, \widehat{\mathcal{V}}_{:,:,i}] = \texttt{svd}(\widehat{\mathcal{A}}_{:,:,i}) \\ &\mathcal{U} = \widehat{\mathcal{U}} \times_{3} \boldsymbol{M}^{-1}, \ \mathcal{S} = \widehat{\mathcal{S}} \times_{3} \boldsymbol{M}^{-1}, \ \mathcal{V} = \widehat{\mathcal{V}} \times_{3} \boldsymbol{M}^{-1}. \end{split}$$

Perfectly (i.e. embarrassingly) parallelizable! For face *i*, exist singular values $\hat{\sigma}_i^{(j)}$, $j = 1, ..., \rho_i$ Need definition of a Gaussian Random Tensor, \mathcal{W} , then consider $\mathcal{A} * \mathcal{W}$:



Exercise: Verify that each frontal slice of $\widehat{\mathcal{W}}$ is the same.

Zhang, Saibaba, Kilmer, Aeron, NLAA, 2018

Randomized t-SVD with Subspace-type Iteration

Input $\mathcal{A} \in \mathbb{R}^{m \times \ell \times n}$, target truncation term k, oversampling parameter p, the number of iterations q

Output $\mathcal{U}_k \in \mathbb{R}^{m \times k \times n}$, $\mathcal{S}_k \in \mathbb{R}^{k \times k \times n}$, and $\mathcal{V}_k \in \mathbb{R}^{\ell \times k \times n}$

• Generate a Gaussian random tensor $\mathcal{W} \in \mathbb{R}^{\ell \times (k+p) \times n}$

• Form
$$\mathcal{Y} = (\mathcal{A} * \mathcal{A}^{\top})^q * \mathcal{A} * \mathcal{W};$$

- Form tensor QR factorization $\mathcal{Y} = \mathcal{Q} * \mathcal{R}$;
- Form a tensor $\mathcal{B} = \mathcal{Q}^{\top} * \mathcal{A}$, the size of \mathcal{B} is $(k+p) \times \ell \times n$;
- Compute t-SVD of \mathcal{B} , truncate it, and obtain $\mathcal{B}_k = \mathcal{U}_k * \mathcal{S}_k * \mathcal{V}_k^{\top}$;
- Form the rt-SVD of $\mathcal{A}, \ \mathcal{A} \approx (\mathcal{Q} * \mathcal{B}_k) = (\mathcal{Q} * \mathcal{U}_k) * \mathcal{S}_k * \mathcal{V}_k^{\top}.$

In practice, implemented in transform domain, with parallel matrix computations.

Analysis: Expectation of Error

Implemented in transform domain, different iter count q_i per face.

Theorem

The output satisfies

$$egin{array}{rll} \mathbb{E} \| \mathcal{A} - \mathcal{Q} * \mathcal{Q}^{ op} * \mathcal{A} \|^2 &\leq & \mathbb{E} \| \mathcal{A} - \mathcal{Q} * \mathcal{B}_k \|^2 \ &\leq & rac{1}{n} \left(\sum_{i=1}^n \left(1 + rac{k(au_k^{(i)})^{4q_i}}{p-1}
ight) \left(\sum_{j > k} (\widehat{\sigma}_j^{(i)})^2
ight)
ight), \end{array}$$

where k is a target truncation term, $p \ge 2$ is the oversampling parameter, **q** is the iterations count vector, and the singular value gap $\tau_k^{(i)} = \frac{\widehat{\sigma}_{k+1}^{(i)}}{\widehat{\sigma}_k^{(i)}} \ll 1$.

If the term in blue were 1, then optimal.

Zhang, Saibaba, Kilmer, Aeron, NLAA, 2018

Impact on Recognition Rate: Cropped Yale B, k = 25

| | fold 1 | fold 9 | fold 10 | | | | |
|----------------------------|------------------------|--------|---------|--|--|--|--|
| t-SVD | | | | | | | |
| | 0.9912 | 0.7368 | 0.9825 | | | | |
| | rt-S | SVD | | | | | |
| min | 0.9912 | 0.7368 | 0.9737 | | | | |
| mean | 0.9912 | 0.7368 | 0.9772 | | | | |
| max | 0.9912 | 0.7368 | 0.9912 | | | | |
| | $	ext{rt-SVD} \ q = 1$ | | | | | | |
| min | 0.9912 | 0.7368 | 0.9737 | | | | |
| mean | 0.9912 | 0.7368 | 0.9833 | | | | |
| max | 0.9912 | 0.7368 | 0.9912 | | | | |
| $\operatorname{rt-SVD}q=2$ | | | | | | | |
| min | 0.9912 | 0.7368 | 0.9825 | | | | |
| mean | 0.9912 | 0.7368 | 0.9882 | | | | |
| max | 0.9912 | 0.7368 | 0.9912 | | | | |

t-product applications

Application: Facial Recognition



 $\vec{\mathcal{A}}_j$ is mean subtracted image

- $\vec{\mathcal{X}}_{j}, j = 1, 2, \dots, m$ are the training images
- $\vec{\mathcal{Y}}$ is the mean image
- $\vec{\mathcal{A}}_j = \vec{\mathcal{X}}_j \vec{\mathcal{Y}}$ has the mean-subtracted images
- $\mathcal{K} = \mathcal{A} * \mathcal{A}^{\top} = \mathcal{U} * \mathcal{S} * \mathcal{S}^{\top} * \mathcal{U}^{\top}$ is the covariance tensor
- Left orthogonal \mathcal{U} contains the principal components, so

$$\vec{\mathcal{A}}_{j} \approx \mathcal{U}_{:,1:k,:} * \underbrace{(\mathcal{U}_{:,1:k,:}^{\top} * \vec{\mathcal{A}}_{j})}_{\text{tensor coefs}}$$

• Note $\mathcal{U}_{:,1:k,:} * \mathcal{U}_{:,1:k,:}^{\top}$ is orthogonal projection tensor.

We keep the basis $\mathcal{U}_{:,1:k,:}$ and the tensor coefficients $\mathcal{U}_{:,1:k,:}^{\top} * \vec{\mathcal{A}}_{j}$.

When a new (mean subtracted) image, oriented as a tensor, $\vec{\mathcal{B}}$, comes in, we compute its tensor coefficients $\mathcal{U}_{:,1:k,:}^{\top} * \vec{\mathcal{B}}$

Then we look for the image with the smallest Frobenius norm difference with the tensor coefficients in the database.

This is fundamentally different treatment than "eigenfaces."

Facial Recognition Task



Take 256 image subset (4 people, 64 different lighting conditions).

Randomly removed 1 image per person.

The Extended Yale Face Database B, http://vision.ucsd.edu/~leekc/ExtYaleDatabase/ExtYaleB.html

Facial Recognition

 \mathcal{A} is $192 \times 252 \times 128$. Truncated to k = 15. $\frac{\|\mathcal{A} - \widehat{\mathcal{A}}\|}{\|\mathcal{A}\|} = .115$ Recall, this means

$$\mathcal{A} \approx \mathcal{U}_{:,1:k,:} * (\mathcal{S}_{1:k,1:k,:} * \mathcal{V}_{:,1:k,:}^{\top}) = \mathcal{U}_{:,1:k,:} * \underbrace{(\mathcal{U}_{:,1:k,:}^{\top} * \mathcal{A})}_{\mathcal{C}},$$

so the *j*th lateral slice, a (mean subtracted) image, is $\mathcal{A}_{:,j,:} = \sum_{i=1}^{k} \mathcal{U}_{:,i,:} * \mathbf{c}_{i,j}$.



Difference image of first slice:

Facial Recognition

Interpretability: The $\mathcal{U}_{:,i,:}$ are the basis elements, do we expect they look like ghost images as in eigenfaces?



Exercise: How much (implicit) storage is required for the training data, and what is the ratio of this to the storage for \mathcal{A} ?

Facial Recognition

Not necessarily - remember, these are NOT linear combinations anymore.



Exercise: How much (implicit) storage is required for the training data, and what is the ratio of this to the storage for \mathcal{A} ?

- How well does the matrix PCA approximation to k = 15 terms compare? The relative error is about $2 \times$ as large!
- All 4 test cases were correctly identified by the tensor-based PCA approach. Only 3 of the 4 were correctly identified by the matrix-based PCA approach.
- Same data, treated differently!

Facial Recognition Task, Revisited \boldsymbol{M} is DFT

- Experiment 1: randomly select 15 images of each person as training, test all remaining images
- Experiment 2: randomly selected 5 images of each person as training, test all remaining images
- 20 trials for each experiment



Results from Hao, et al, SIIMS, 2013

t-SVDII vs. PCA



Yale Example



Kilmer, Horesh, Avron, Newman, Tensor-tensor products for optimal representation and compression, (2021)

Truncated-HOSVD in the \star_M Framework

Define $\boldsymbol{M} = (\mathbf{U}^{(3)})^{\top}$ from the HOSVD

Then we can express the HOSVD in the \star_M tensor framework!

We can show that the t-SVDM, t-SVDMII are superior to tr-HOSVD for appropriate truncation levels, as well.

Hyperspectral Results



Figure: Hyperspectral compression vs. relative error. Best performance are points lying closest to the upper left; i.e., the most compression for the smallest relative error.

Numerical Results

Approximation of hyperspectral wavelength 10, corresponds to upper right of graph.

Original

t-SVDMII, $\gamma = 0.94$



tr-HOSVD(10, 10, 10) tr-HOSVD(14, 14, 14)





Neural Networks, Hypothetically

Let a_0 be a **feature vector** with an associated **target vector** cLet f be a function which propagates a_0 though connected layers:

$$\boldsymbol{a}_{j+1} = \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1,$$

where σ is some **nonlinear**, monotonic activation function

Neural Networks, Hypothetically

Let a_0 be a **feature vector** with an associated **target vector** cLet f be a function which propagates a_0 though connected layers:

$$\boldsymbol{a}_{j+1} = \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1,$$

where σ is some **nonlinear**, **monotonic activation** function

Goal: Learn the function f which optimizes:

$$\min_{f \in \mathcal{H}} E(f) \equiv \frac{1}{m} \sum_{i=1}^{m} \underbrace{V(\boldsymbol{c}^{(i)}, f(\boldsymbol{a}_{0}^{(i)}))}_{\text{loss function}} + \underbrace{R(f)}_{\text{regularizer}}$$

 ${\mathcal H}$ - hypothesis space of functions

Neural Networks, Hypothetically

Let a_0 be a **feature vector** with an associated **target vector** cLet f be a function which propagates a_0 though connected layers:

$$\boldsymbol{a}_{j+1} = \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1,$$

where σ is some **nonlinear**, **monotonic activation** function

Goal: Learn the function f which optimizes:

$$\min_{f \in \mathcal{H}} E(f) \equiv \frac{1}{m} \sum_{i=1}^{m} \underbrace{V(\boldsymbol{c}^{(i)}, f(\boldsymbol{a}_{0}^{(i)}))}_{\text{loss function}} + \underbrace{R(f)}_{\text{regularizer}}$$
$$\mathcal{H} \text{ - hypothesis space of functions}$$
rich, restrictive, efficient

CSE 392/CS 395T/M 397C

Less is More: Reduced Parameterization

Given an $n \times n$ image A_0 , stored as $\boldsymbol{a}_0 \in \mathbb{R}^{n^2 \times 1}$ and $\vec{\mathcal{A}}_0 \in \mathbb{R}^{n \times 1 \times n}$.



Tensor:

$$\vec{\mathcal{A}}_{j+1} = \sigma(\mathcal{W}_j * \vec{\mathcal{A}}_j + \vec{\mathcal{B}}_j)$$

$$\boxed{\boldsymbol{n^3 + n^2 \text{ parameters}}}$$



bi

Tensor Neural Networks (tNNs)

Forward propagation



Update parameters

Objective function

Backward propagation

M. Nielsen, Neural networks and deep learning, 2017



M. Nielsen, Neural networks and deep learning, 2017



M. Nielsen, Neural networks and deep learning, 2017



where $\vec{\mathcal{Z}}_{j+1} = \mathcal{W}_j * \vec{\mathcal{A}}_j + \vec{\mathcal{B}}_j$ and \odot is the pointwise product

$$\delta \vec{\mathcal{A}}_j := \frac{\partial E}{\partial \vec{\mathcal{A}}_j}$$

M. Nielsen, Neural networks and deep learning, 2017



$$\delta \vec{\mathcal{A}}_j := \frac{\partial E}{\partial \vec{\mathcal{A}}_j} = \frac{\partial E}{\partial \vec{\mathcal{A}}_{j+1}} \frac{\partial \vec{\mathcal{A}}_{j+1}}{\partial \vec{\mathcal{Z}}_{j+1}} \frac{\partial \vec{\mathcal{Z}}_{j+1}}{\partial \vec{\mathcal{A}}_j}$$

M. Nielsen, Neural networks and deep learning, 2017



where $\vec{\mathcal{Z}}_{j+1} = \mathcal{W}_j * \vec{\mathcal{A}}_j + \vec{\mathcal{B}}_j$ and \odot is the pointwise product

M. Nielsen, Neural networks and deep learning, 2017



where $\vec{\mathcal{Z}}_{j+1} = \mathcal{W}_j * \vec{\mathcal{A}}_j + \vec{\mathcal{B}}_j$ and \odot is the pointwise product

Update parameters = Gradient descent!

M. Nielsen, Neural networks and deep learning, 2017

Mimetic Structure

- The **update relations** are **analogous** to their matrix counterparts by **no coincidence**
- In the **M-product** framework, tensors are **M-linear** operators just as **matrices** are **linear** operators

A Dynamic Perspective on Neural Networks

Consider a residual network matrix forward propagation scheme:

$$\boldsymbol{a}_{j+1} = \boldsymbol{a}_j + h \, \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1$$

This is a **forward Euler** discretization of the continuous system:

 $\dot{\boldsymbol{a}}(t) = \sigma(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t)) \text{ for } t \in [0, T]$

Haber and Ruthotto, Inverse Problems, 2017

He, Zhang, and Ren, CVPR, 2015

A Dynamic Perspective on Neural Networks

Consider a **residual network** matrix **forward propagation** scheme:

$$\boldsymbol{a}_{j+1} = \boldsymbol{a}_j + h \, \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1$$

This is a **forward Euler** discretization of the continuous system:

$$\dot{\boldsymbol{a}}(t) = \sigma(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t)) \text{ for } t \in [0, T]$$

Network layers are discrete steps in time!

Haber and Ruthotto, Inverse Problems, 2017

He, Zhang, and Ren, CVPR, 2015

A Dynamic Perspective on Neural Networks

Consider a **residual network** matrix **forward propagation** scheme:

$$\boldsymbol{a}_{j+1} = \boldsymbol{a}_j + h \, \sigma(W_j \cdot \boldsymbol{a}_j + \boldsymbol{b}_j) \text{ for } j = 0, \dots, N-1$$

This is a **forward Euler** discretization of the continuous system:

 $\dot{\boldsymbol{a}}(t) = \sigma(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t)) \text{ for } t \in [0, T]$

Network layers are discrete steps in time!

Well-posed learning problem

- Forward propagation is **stable**. Converge to a solution
- Classification function depends continuously on initialization of parameters. Distinctions remain distinct

Haber and Ruthotto, Inverse Problems, 2017

He, Zhang, and Ren, CVPR, 2015

In the continuous case, $\dot{\boldsymbol{a}}(t) = \sigma(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t))$, stability depends on the eigenvalues of the Jacobian:

$$J(t) = W(t)^\top \cdot \operatorname{diag}(\sigma'(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t)))$$

Haber and Ruthotto, Inverse Problems, 2017

In the continuous case, $\dot{\boldsymbol{a}}(t) = \sigma(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t))$, stability depends on the eigenvalues of the Jacobian:

$$J(t) = W(t)^{\top} \cdot \operatorname{diag}(\sigma'(W(t) \cdot \boldsymbol{a}(t) + \boldsymbol{b}(t)))$$

Well-posed Learning Problem

 $\max_{i} \operatorname{Re}(\lambda_{i}(W(t))) \leq 0 \Longrightarrow \text{ stable forward propagation}$ $\max_{i} \operatorname{Re}(\lambda_{i}(W(t))) \approx 0 \Longrightarrow \text{ distinctions remain distinct}$

Haber and Ruthotto, Inverse Problems, 2017

In the continuous case, $\dot{\vec{\mathcal{A}}}(t) = \sigma(\mathcal{W}(t) * \vec{\mathcal{A}}(t) + \vec{\mathcal{B}}(t))$, stability depends on the **eigenvalues of the Jacobian:**

 $J(t) = \texttt{bcirc}(\mathcal{W}(t))^\top \cdot \texttt{diag}(\sigma'(\texttt{unfold}(\mathcal{W}(t) * \vec{\mathcal{A}}(t) + \vec{\mathcal{B}}(t))))$

Well-posed Learning Problem

 $\max_{i} \operatorname{Re}(\lambda_{i}(\operatorname{bcirc}(\mathcal{W}(t)))) \leq 0 \Longrightarrow \text{ stable forward propagation} \\ \max_{i} \operatorname{Re}(\lambda_{i}(\operatorname{bcirc}(\mathcal{W}(t)))) \approx 0 \Longrightarrow \text{ distinctions remain distinct}$

Haber and Ruthotto, Inverse Problems, 2017

In the continuous case, $\dot{\vec{\mathcal{A}}}(t) = \sigma(\mathcal{W}(t) * \vec{\mathcal{A}}(t) + \vec{\mathcal{B}}(t))$, stability depends on the **eigenvalues of the Jacobian:**

 $J(t) = \texttt{bcirc}(\mathcal{W}(t))^\top \cdot \texttt{diag}(\sigma'(\texttt{unfold}(\mathcal{W}(t) * \vec{\mathcal{A}}(t) + \vec{\mathcal{B}}(t))))$

Well-posed Learning Problem

 $\max_{i} \operatorname{Re}(\lambda_{i}(\operatorname{bcirc}(\mathcal{W}(t)))) \leq 0 \Longrightarrow \text{ stable forward propagation} \\ \max_{i} \operatorname{Re}(\lambda_{i}(\operatorname{bcirc}(\mathcal{W}(t)))) \approx 0 \Longrightarrow \text{ distinctions remain distinct}$

Implement stable forward propagation scheme which ensures well-posedness!

Haber and Ruthotto, Inverse Problems, 2017

A Hamiltonian-Inspired Framework

Definition (Hamiltonian)

A system $H(\boldsymbol{a}(t), \boldsymbol{z}(t))$ which satisfies $\dot{\boldsymbol{a}}(t) = \nabla_{\boldsymbol{z}} H$ and $\dot{\boldsymbol{z}}(t) = -\nabla_{\boldsymbol{a}} H$

Physical Intuition: a = position, z = velocity/momentum

$$H(\boldsymbol{a}(t), \boldsymbol{z}(t)) = \underbrace{\frac{1}{2}\boldsymbol{z}(t)^{\top} \cdot \boldsymbol{z}(t)}_{\text{kinetic}} + \underbrace{U(\boldsymbol{a}(t))}_{\text{potential}}$$

Properties:

- Time reversibility \rightarrow backward propagation
- ${\bf Energy\ conservation} \quad \rightarrow \quad {\rm stable\ forward\ propagation}$

Volume preservation \rightarrow distinctions remain distinct

Seamless Matrix to Tensor Reformulation of Complex Architectures

Consider the symmetrized, Hamiltonian-inspired system:

$$\frac{\mathrm{d}}{\mathrm{d}t} \begin{bmatrix} \boldsymbol{a}(t) \\ \boldsymbol{z}(t) \end{bmatrix} = \sigma \left(\begin{bmatrix} 0 & W(t) \\ -W(t)^{\top} & 0 \end{bmatrix} \cdot \begin{bmatrix} \boldsymbol{a}(t) \\ \boldsymbol{z}(t) \end{bmatrix} + \begin{bmatrix} -\boldsymbol{b}(t) \\ \boldsymbol{b}(t) \end{bmatrix} \right)$$

The system is antisymmetric and hence inherently stable

E. Haber, L. Ruthotto, Stable architectures for deep neural networks, Inverse Problems, 2017

L. Newman, L. Horesh, H. Avron, M. Kilmer, Stable tensor neural networks for rapid deep learning, arxiv 1811.06569, 2018

Seamless Matrix to Tensor Reformulation of Complex Architectures

Consider the symmetrized, Hamiltonian-inspired system:

$$\frac{\mathrm{d}}{\mathrm{d}t} \begin{bmatrix} \boldsymbol{a}(t) \\ \boldsymbol{z}(t) \end{bmatrix} = \sigma \left(\begin{bmatrix} 0 & W(t) \\ -W(t)^\top & 0 \end{bmatrix} \cdot \begin{bmatrix} \boldsymbol{a}(t) \\ \boldsymbol{z}(t) \end{bmatrix} + \begin{bmatrix} -\boldsymbol{b}(t) \\ \boldsymbol{b}(t) \end{bmatrix} \right)$$

The system is antisymmetric and hence inherently stable

We discretize with leapfrog integration which is stable for purely imaginary eigenvalues:

$$\boldsymbol{z}_{j+\frac{1}{2}} = \boldsymbol{z}_{j-\frac{1}{2}} - h \, \sigma(W_j^\top \cdot \boldsymbol{a}_j + \boldsymbol{b}_j),$$
$$\boldsymbol{a}_{j+1} = \boldsymbol{a}_j + h \, \sigma(W_j \cdot \boldsymbol{z}_{j+\frac{1}{2}} + \boldsymbol{b}_j)$$

E. Haber, L. Ruthotto, Stable architectures for deep neural networks, Inverse Problems, 2017

L. Newman, L. Horesh, H. Avron, M. Kilmer, Stable tensor neural networks for rapid deep learning, arxiv 1811.06569, 2018

Seamless Matrix to Tensor Reformulation of Complex Architectures

Consider the symmetrized, Hamiltonian-inspired system:

$$\frac{\mathrm{d}}{\mathrm{d}t} \begin{bmatrix} \vec{\mathcal{A}}(t) \\ \vec{\mathcal{Z}}(t) \end{bmatrix} = \sigma \left(\begin{bmatrix} 0 & \mathcal{W}(t) \\ -\mathcal{W}(t)^{\top} & 0 \end{bmatrix} * \begin{bmatrix} \vec{\mathcal{A}}(t) \\ \vec{\mathcal{Z}}(t) \end{bmatrix} + \begin{bmatrix} -\vec{\mathcal{B}}(t) \\ \vec{\mathcal{B}}(t) \end{bmatrix} \right)$$

The system is antisymmetric and hence inherently stable

We discretize with leapfrog integration which is stable for purely imaginary eigenvalues:

$$\vec{\mathcal{Z}}_{j+\frac{1}{2}} = \vec{\mathcal{Z}}_{j-\frac{1}{2}} - h \,\sigma(\mathcal{W}_j^\top * \vec{\mathcal{A}}_j + \vec{\mathcal{B}}_j),$$
$$\vec{\mathcal{A}}_{j+1} = \vec{\mathcal{A}}_j + h \,\sigma(\mathcal{W}_j * \vec{\mathcal{Z}}_{j+\frac{1}{2}} + \vec{\mathcal{B}}_j)$$

E. Haber, L. Ruthotto, Stable architectures for deep neural networks, Inverse Problems, 2017

L. Newman, L. Horesh, H. Avron, M. Kilmer, Stable tensor neural networks for rapid deep learning, arxiv 1811.06569, 2018

Tensor vs. Matrix Learning: MNIST Database Results

Data: 28 × 28 grayscale images of handwritten digits, 60000 train, 10000 test **Fixed parameters:** h = 0.1, $\alpha = 0.1$, $\sigma = tanh$, batch size = 20, 100 epochs **Learnable parameters:** matrix - $28^4N + 28^2N$, tensor - $28^3N + 28^2N$



L. Newman, L. Horesh, H. Avron, M. Kilmer, Stable tensor neural networks for rapid deep learning, 2018, https://arxiv.org/abs/1811.06569

UT Austin

CSE 392/CS 395T/M 397C

Tensor vs. Matrix Learning: CIFAR-10 Database Results

Data: $32 \times 32 \times 3$ RGB images from 10 classes, 50000 train, 10000 test **Fixed parameters:** h = 0.1, $\alpha = 0.01$, $\sigma = tanh$, batch = 100, 300 epochs, M = DCT matrix. **Learnable parameters:** $mat-(3^2 \cdot 32^4)N + 3 \cdot 32^2N$, ten- $(3^2 \cdot 32^3)N + 3 \cdot 32^2N$



A. Krizhevsky, Learning multiple layers of features from tiny images, 2009

L. Newman, L. Horesh, H. Avron, M. Kilmer, Stable tensor neural networks for rapid deep learning, arxiv 1811.06569, 2018

Dynamic Graphs

- Graphs are ubiquitous data structures represent interactions and structural relationships
- In many real-world applications, underlying graph changes over time
- Learning representations of dynamic graphs is essential



Dynamic Graphs - Applications



Corporate/financial networks, Natural Language Understanding (NLU), Social networks, Neural activity networks, Traffic predictions.

UT Austin

CSE 392/CS 395T/M 397C

Graph Convolutional Networks

- Graph Neural Networks (GNN) popular tools to explore graph structured data
- Graph Convolutional Networks (GCN) based on graph convolution filters extend convolutional neural networks (CNNs) to irregular graph domains
- $\bullet\,$ These GNN models operate on a given, static graph



Courtesy: Image by (Kipf & Welling, 2016).

UT Austin

CSE 392/CS 395T/M 397C

Graph Convolutional Networks

Motivation:

• Convolution of two signals x and y:

$$\boldsymbol{x} \otimes \boldsymbol{y} = \boldsymbol{F}^{-1}(\boldsymbol{F}\boldsymbol{x} \odot \boldsymbol{F}\boldsymbol{y}),$$

 \boldsymbol{F} is Fourier transform (DFT matrix)

• Convolution of two node signals x and y on a graph with Laplacian $L = U \Lambda U^{\top}$:

$$oldsymbol{x} \otimes oldsymbol{y} = oldsymbol{U}(oldsymbol{U}^{ op}oldsymbol{x} \odot oldsymbol{U}^{ op}oldsymbol{y})$$

• Filtered convolution:

$$\boldsymbol{x} \otimes_{filt} \boldsymbol{y} = h(\boldsymbol{L})\boldsymbol{x} \odot h(\boldsymbol{L})\boldsymbol{y},$$

with matrix filter function $h(\boldsymbol{L}) = \boldsymbol{U}h(\Lambda)\boldsymbol{U}^{\top}$

Graph Convolutional Neural Networks

• Layer of initial convolution based GNNs (Bruna et. al, 2016): Given graph Laplacian $\boldsymbol{L} \in \mathbb{R}^{N \times N}$ and node features $\boldsymbol{X} \in \mathbb{R}^{N \times F}$:

$$\boldsymbol{H}_{i+1} = \sigma(h_{\theta}(\boldsymbol{L})\boldsymbol{H}_{i}\boldsymbol{W}^{(i)}),$$

 h_{θ} filter function parametrized by θ , σ a nonlinear function (e.g., RELU), and $W^{(i)}$ a weight matrix with $H_0 = X$

• Defferrard et al., (2016) used Chebyshev approximation $T_{m+1}(L) = 2LT_m(L) - T_{m-1}(L)$:

$$h_{\theta}(\boldsymbol{L}) = \sum_{k=0}^{K} \theta_k T_k(\boldsymbol{L})$$

- GCN (Kipf & Welling, 2016): Each layer takes form: $\sigma(\boldsymbol{LXW})$
- 2-layer example:

$$oldsymbol{Z} = ext{softmax}(oldsymbol{L} \, \sigma(oldsymbol{L} oldsymbol{X} oldsymbol{W}^{(0)}) \, oldsymbol{W}^{(1)})$$

UT Austin

CSE 392/CS 395T/M 397C

GCN for Dynamic Graphs

- We consider *time varying*, or *dynamic*, graphs
- **Goal:** Extend GCN framework to the dynamic setting for tasks such as node and edge classification, link prediction
- How ?

GCN for Dynamic Graphs

- We consider *time varying*, or *dynamic*, graphs
- **Goal:** Extend GCN framework to the dynamic setting for tasks such as node and edge classification, link prediction
- How ? Use a tensor-tensor framework!
- T adjacency matrices $A_{::t} \in \mathbb{R}^{N \times N}$ stacked into tensor $\mathcal{A} \in \mathbb{R}^{N \times N \times T}$
- T node feature matrices $\boldsymbol{X}_{::t} \in \mathbb{R}^{N \times F}$ stacked into tensor $\mathcal{X} \in \mathbb{R}^{N \times F \times T}$

TM-GCN



TM-GCN

- We use the \star_M -Product to extend the std. GCN to dynamic graphs
- We propose tensor GCN model $\sigma(\mathcal{A} \star_M \mathcal{X} \star_M \mathcal{W})$
- 2-layer example:

$$\mathcal{Z} = \operatorname{softmax}(\mathcal{A} \star_M \sigma(\mathcal{A} \star_M \mathcal{X} \star_M \mathcal{W}^{(0)}) \star_M \mathcal{W}^{(1)})$$

 $\bullet\,$ We choose M to be lower triangular and banded (causal):



• Can be shown to be consistent with a spatio-temporal message passing model

Theoretical Motivation

- The tensor \mathcal{A} has an eigendecomposition $\mathcal{A} = \mathcal{Q} \star \mathcal{D} \star \mathcal{Q}^{\top}$.
- Filtering: Given a signal $\mathcal{X} \in \mathbb{R}^{N \times 1 \times T}$ and a function $g : \mathbb{R}^{1 \times 1 \times T} \to \mathbb{R}^{1 \times 1 \times T}$, we define the tensor spectral graph filtering of \mathcal{X} with respect to g as

$$\mathcal{X}_{\text{filt}} = \mathcal{Q} \star g(\mathcal{D}) \star \mathcal{Q}^{\top} \star \mathcal{X},$$

where

$$g(\mathcal{D})_{mn:} = \begin{cases} g(\mathcal{D}_{mn:}) & \text{if } m = n, \\ 0 & \text{if } m \neq n. \end{cases}$$

• Suppose g satisfies above. For any $\varepsilon > 0$, there exists an integer K and a set $\{\theta^{(k)}\}_{k=1}^K \subset \mathbb{R}^{1 \times 1 \times T}$ such that

$$\left\|g(\mathcal{D}) - \sum_{k=0}^{K} \mathcal{D}^{\star k} \star \theta^{(k)}\right\| < \varepsilon, \tag{1}$$

where $\|\cdot\|$ is the tensor Frobenius norm, and where $\mathcal{D}^{\star k} = \mathcal{D} \star \cdots \star \mathcal{D}$ is the M-product of k instances of \mathcal{D} , with the convention that $\mathcal{D}^{\star 0} = \mathcal{J}$

$\ensuremath{\operatorname{TensorGCN}}$ - $\ensuremath{\operatorname{Datasets}}$

Table: Dataset statistics. By partitioning the data into windows of the specified length results in the given number of graphs.

| | | | | | | Partitioning | | |
|----------------------|-----------|-----------------|------------|---------------|---------|----------------------|---------------|-------------------|
| Dataset | Nodes | Edges | No. graphs | Window length | Classes | S_{train} | $S_{\rm val}$ | S_{test} |
| SBM | 1,000 | $1,\!601,\!999$ | 50 | - | - | 35 | 5 | 10 |
| BitcoinOTC | 6,005 | 35,569 | 135 | 14 | 2 | 95 | 20 | 20 |
| BitcoinAlpha | $7,\!604$ | $24,\!173$ | 135 | 14 | 2 | 95 | 20 | 20 |
| Reddit | $3,\!818$ | $163,\!008$ | 86 | 14 | 2 | 66 | 10 | 10 |
| Chess | $7,\!301$ | $64,\!958$ | 100 | 31 | 3 | 80 | 10 | 10 |



Partitioning of \mathcal{A} into training, validation and testing data.

TM-GCN - Edge Classification Results

| Table: Results for edge classification. | Performance measures | is | F1 | score. |
|---|----------------------|----|----|--------|
|---|----------------------|----|----|--------|

| | Dataset | | | | | |
|----------------------|-------------|---------------|--------|--------|--|--|
| Method | Bitcoin OTC | Bitcoin Alpha | Reddit | Chess | | |
| WD-GCN | 0.3562 | 0.2533 | 0.2337 | 0.4311 | | |
| EvolveGCN | 0.3483 | 0.2273 | 0.2012 | 0.4351 | | |
| GCN | 0.3402 | 0.2381 | 0.1968 | 0.4342 | | |
| TM- GCN - $M1$ | 0.3660 | 0.3243 | 0.2057 | 0.4708 | | |
| TM- GCN - $M2$ | 0.4361 | 0.2466 | 0.1833 | 0.4513 | | |

F1 score =
$$2 \cdot \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}}$$

| TICD | |
|------|--------|
| | Austin |
| | |

TM-GCN - Link Prediction Results

| | | | Dataset | | |
|----------------------|--------|-------------|---------------|--------|--------|
| Method | SBM | Bitcoin OTC | Bitcoin Alpha | Reddit | Chess |
| WD-GCN | 0.9436 | 0.8071 | 0.8795 | 0.3896 | 0.1279 |
| EvolveGCN | 0.7620 | 0.6985 | 0.7722 | 0.2866 | 0.0915 |
| GCN | 0.9201 | 0.6847 | 0.7655 | 0.3099 | 0.0899 |
| TM- GCN - $M1$ | 0.9684 | 0.8026 | 0.9318 | 0.2270 | 0.1882 |
| TM- GCN - $M2$ | 0.9799 | 0.8458 | 0.9631 | 0.1405 | 0.1514 |

Table: Results for link prediction. Performance measure is Mean Average Precision (MAP).

$$\label{eq:precision} \begin{split} \text{precision} &= \frac{\text{true positive}}{\text{true positive} + \text{false positive}}\\ \text{recall} &= \frac{\text{true positive}}{\text{true positive} + \text{false negative}} \end{split}$$

Questions?